

527,715

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036310 A1

(51) International Patent Classification⁷: **G03B 21/56**

(21) International Application Number:
PCT/KR2003/002172

(22) International Filing Date: 17 October 2003 (17.10.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2002-0065041 21 October 2002 (21.10.2002) KR

(71) Applicant and

(72) Inventor: **CHOI, Hae-Yong** [KR/KR]; Mookdong I
Park Apartment #108-301, 385 Mook-dong, Jungnang-ku,
Seoul-city 131-768 (KR).

(74) Agent: **CHOI, Dall-Ryong**; Rm# 506 Poonglim Bldg.,
823-1 Yoksam-dong, Kangnam-ku, Seoul-city 135-784
(KR).



(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: BOTH-SIDE IMAGE FILM SCREEN



(57) Abstract: Disclosed is a double-sided image film screen including a plastic material having a high optical transmission property and a light-refracting material, made of silica, having an optical transmission property and a refractivity of 1.4~2.5, wherein a content and a particle size of the light-refracting material and a thickness of the film screen are designated such that an image incident on the film screen by means of light projected from a projector is dividedly displayed on front and rear surfaces of the film screen, thereby displaying the image formed thereon through the front and rear surfaces thereof, increasing the visibility of the image and eliminating a hot spot generated by a projection light source of the projector. Compared to conventional screens, the double-sided image film screen is advantageous in that it displays the image through the front and rear surfaces thereof.

WO 2004/036310 A1